

# PRODIGY®



Prodigy shown with Ice Gray shell



Prodigy shown with Ice Gray shell /  
Monterey Gray cabinet

<b>Seating Capacity</b>	5 adults
<b>Dimensions</b>	6'6" x 7' x 33"/1.98m x 2.13m x .84m
<b>Water Capacity</b>	325 gallons/1,230 liters
<b>Weight</b>	645 lbs./293 kg dry; 4,231 lbs./1,919 kg filled*
<b>Spa Shell Options</b>	Alpine White, Crème, Ice Gray, Platinum, Tuscan Sun or Desert**
<b>Cabinet Options</b>	Everwood® HD: Mocha, Monterey Gray or Teak**
<b>Jets - 22 (w/ Stainless Steel Trim)</b>	1 Moto-Massage® DX jet (2) 2 SoothingStream® jets 1 JetStream® jets 2 Rotary Hydromassage jets 1 Directional Hydromassage jets 14 Directional Precision® jets
<b>Water Care System (Optional)</b>	ACE® Salt Water Sanitizing System or EverFresh® System
<b>Jet Pump</b>	Wavemaster® 7000; One-speed, 1.65 HP Continuous Duty, 3.5 HP Breakdown Torque
<b>Circulation Pump</b>	SilentFlo 5000® for quiet, continuous filtration
<b>Effective Filtration Area</b>	90 sq. ft., top loading 100% no-bypass filtration
<b>Ozone System</b>	FreshWater® III Corona Discharge
<b>Control System</b>	IQ 2020® with LCD control panel 115v/20amp, (includes G.F.C.I. protected power cord) or 230v/50amp, 60Hz***
<b>Lighting System</b>	Luminescence® multi-color four-zone
<b>Heater</b>	No-Fault®, 1500w/115v or 6000w/230v
<b>Energy Efficiency</b>	Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law
<b>Vinyl Cover</b>	3.5" to 2.5" tapered, 2 lb. density foam core, with hinge seal in Caramel, Chocolate, Slate, or Evergreen
<b>Cover Lifter (Optional)</b>	CoverCradle®, CoverCradle II, Lift 'n Glide® or UpRite®
<b>Steps (Optional)</b>	Everwood® HD, NXT, or Polymer
<b>Entertainment System (Optional)</b>	Wireless Sound System

\* Includes water and 5 adults weighing 175 lbs. each  
\*\*Some color combinations are considered special orders. Ice Gray/Teak, Crème/Monterey Gray, Desert/Monterey Gray and Platinum/Teak have special order pricing. See your dealer for details.  
\*\*\*G.F.C.I. protected sub-panel required in 230v mode  
Export models available in 230v, 50Hz, 1500w Heater , Tri-X® filters