

# VACANZA<sup>®</sup> SERIES

## Tarino<sup>™</sup>



Tarino shown in Arctic White shell



Tarino shown with Arctic White shell and Parchment cabinet

### DIMENSIONS

<b>Seating Capacity</b>	5 adults
<b>Dimensions</b>	6'10" x 6'10" x 33"
<b>Water Capacity</b>	310 gallons / 1,175 liters
<b>Weight</b>	Dry: 730 lbs. / 330 kg; Filled*: 4,190 lbs. / 1,905 kg

### PERFORMANCE FEATURES

<b>Jets</b>	23 Jets: 17 Euro 4 AdaptaFlo <sup>®</sup> 2 AdaptaSsage <sup>®</sup>
<b>Pumps</b>	ReliaFlo <sup>®</sup> 1.5 Hp Dual-Speed Pump
<b>Heater</b>	Hi-Flow Heater (1,000/4,000 Watts)
<b>Electrical</b>	115 V / 20 amp or 230 V / 50 amp**
<b>Energy Efficiency</b>	Fully-insulated with FiberCor <sup>®</sup> material, 2 lb. density, CEC-compliant
<b>Smart Spa Technology (Optional)</b>	Caldera Spas App, Powered by the Connected Spa Kit

### WATER CARE

<b>Filtration</b>	30 sq. ft. filter
<b>Water Care System</b>	@ease <sup>™</sup> In-Line System with SmartChlor <sup>™</sup> Technology & Minerals (Cartridge-ready, U.S. Only) or FROG Serene <sup>™</sup> In-Line Bromine & Minerals System (Cartridge-ready)
<b>Ozone System (Optional)</b>	Ozone

### STYLE ENHANCEMENTS

<b>LCD Controls</b>	LCD Control System
<b>Lighting</b>	LED Lighting with 10 Interior Points-of-Light
<b>Water Feature</b>	(1) Acquarella <sup>®</sup> Waterfall
<b>Speakers (Optional)</b>	4 – 1" square
<b>Entertainment (Optional)</b>	Wireless Audio System with BlueTooth <sup>®</sup> Technology
<b>Insulating Cover</b>	3.5" to 2.5" tapered, 2 lb.-density foam core
<b>Cover Lifter Options</b>	ProLift <sup>®</sup> , ProLift <sup>®</sup> II, ProLift <sup>®</sup> III, or ProLift <sup>®</sup> IV
<b>Step Options</b>	EcoTech <sup>®</sup> or Polymer Step in Ash, Java, Parchment

### COLORS

<b>Cover</b>	Chocolate, Slate, Taupe
<b>Spa Shell</b>	Arctic White, White Pearl, Desert, Midnight Canyon, Tuscan Sun
<b>EcoTech<sup>®</sup> Cabinet</b>	Ash, Java, Parchment

\* Filled weight includes the weight of the occupants assuming an average weight of 175 lbs.

\*\* May be field converted for 230V/50 amp operation. This allows heater to operate during low or high-speed pump operation. Requires optional 230v/50 amp GFCI sub-panel.

Product and specifications are subject to change without notice.



[www.CalderaSpas.com](http://www.CalderaSpas.com)