


LIMELIGHT® COLLECTION



FreshWater® IQ
System Ready



Dual Action Filtration
SilentFlo Circulation



FiberCor®
High-Density Insulation



Color LCD Display

FLASH™



*Shown with Alpine White Shell
and Coastal Gray Cabinet*

People	Seating	Jets	Voltage
7 Seats	Open	41 Jets	230 V

Size
7' x 7' x 36" | 213 cm x 213 cm x 91 cm

Water Care
FreshWater®IQ System Ready

LIMELIGHT® COLLECTION

FLASH™



SHELL COLORS*



Alpine White

Desert

Ice Gray

Platinum

Tuscan Sun

CABINET COLORS*




Coastal Gray

Espresso

Sable

COVER COLORS



Black

Storm

LEGENDARY MESSAGE

41 Personalized-Control Jets

- 1 XL Dual Rotary jet
- 3 XL Single Rotary jets
- 1 XL Directional jet
- 4 Standard Single Rotary jets
- 4 Standard Directional jets
- 28 Directional Precision® jets

EASY WATER CARE

Water Care System	FreshWater® IQ System Salt System Ready Smart Monitoring System Optional
Filtration System	Dual action, 100 sq. ft., top loading

LEADING ENERGY EFFICIENCY

Jet Pump 1	Wavemaster® 8200; Two-speed, 2.0 HP Continuous Duty, 4.0 HP Breakdown Torque
Jet Pump 2	Wavemaster® 8000; One-speed, 2.0 HP Continuous Duty, 4.0 HP Breakdown Torque
Circulation Pump	SilentFlo® 5000 Quiet Continuous Filtration
Heater	No-Fault® 4,000 W / 230 V
Insulation	FiberCor® Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas
Cover	WeatherPro™ 4" Tapered Custom-Fit with Hinge Seal

SIZE

Dimensions	7' x 7' x 36" / 213 cm x 213 cm x 91 cm
-------------------	---

CAPACITY

Seating Capacity	7 seats
Water Capacity	360 gallons / 1,365 liters
Weight	845 lbs. / 385 kg dry; 5,070 lbs. / 2,300 kg filled**

ADDITIONAL FEATURES

Smart Spa Technology*	Hot Spring Spas App Powered by the Connected Spa Kit
Water Feature	Vidro® backlit ribbon waterfall
Cover Lifters*	CoverCradle®, CoverCradle II, Lift 'n Glide®, or UpRite®
Steps*	Limelight Collection Step (Coastal Gray, Espresso, and Sable)
Entertainment*	Bluetooth® Wireless Sound System
Control System	IQ 2020® with LCD control panel 230 V / 50 amp, 60 Hz (Includes GFCI protected sub-panel)
Lighting System	Raio® multi-color interior points of light Exterior multi-color lighting with timer
Cooling System*	CoolZone™

*Optional Accessories